

IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the Application:

LISTING OF CLAIMS:

1. (Currently amended) A content distribution system, comprising:
 - a domain name service server which is configured to provide domain name service responses in response to domain name service requests; and
 - a data communications device which is capable of interconnecting between a client and the domain name service server, wherein the data communications device includes:
 - an interface which is capable of communicating with the client, and
 - a controller coupled to the interface, wherein the controller is configured to:
 - intercept a first domain name service request from the client,
 - provide a second domain name service request to the domain name service server through the interface in response to interception of the first domain name service request, the second domain name service request selectively (i) including a client identifier which identifies the client, and (ii) not including the client identifier which identifies the client, based on a selection decision, and
 - convey a domain name service response from the domain name service server to the client through the interface, the domain name service response

including a content server identifier which identifies a content server,

wherein the domain name service server comprises:

an interface which is capable of communicating with the data communications device; and

a controller coupled to the interface, wherein the controller is configured to:

receive the second domain name service request

from the data communications device through the interface, the domain name service request including a data communications device identifier which identifies the data communications device,

select the content server identifier from a

predetermined group of content server identifiers based on (i) a the client identifier which identifies a the client when the second domain name service request further includes the client identifier, and (ii) a the data communications device identifier when the second domain name service request does not include the client identifier, and

provide the domain name service response to the

data communications device through the interface, the domain name service response having the selected content server identifier which identifies a content server.

2. (Original) The content distribution system of claim 1 wherein the second domain name service request includes a domain name field, and wherein the controller of the data communications device includes:

processing circuitry that selectively (i) includes the client identifier in the domain name field of the second domain name service request, and (ii) does not include the client identifier in the domain name field of the

second domain name service request, based on the selection decision, in order to provide the second domain name service request.

3. (Currently amended) A data communications device, comprising:
 - an interface which is capable of communicating with a client; and
 - a controller coupled to the interface, wherein the controller is configured to:
 - intercept a first domain name service request from the client,
 - provide a second domain name service request to a domain name service server through the interface in response to interception of the first domain name service request, the second domain name service request selectively (i) including a client identifier which identifies the client, and (ii) not including the client identifier which identifies the client, based on a selection decision, and
 - convey a domain name service response from the domain name service server to the client through the interface, the domain name service response including a content server identifier which identifies a content server
- wherein the first domain name service request includes a domain name field which contains a domain name, and wherein the controller includes:
- processing circuitry which is configured to generate, as the selection decision, a result having a first value when the domain name belongs to a predetermined group of domain names and a second value when the domain name does not belong to the predetermined group of domain names.

4. (Original) The data communications device of claim 3 wherein the second domain name service request includes a domain name field, and wherein the controller includes:

processing circuitry that selectively (i) includes the client identifier in the domain name field of the second domain name service request, and (ii) does not include the client identifier in the domain name field of the second domain name service request, based on the selection decision, in order to provide the second domain name service request.

5. (Original) The data communications device of claim 4 wherein the processing circuitry is further configured to:

include a flag in the domain name field of the second domain name service request when the client identifier is included in the domain name field of the second domain name service request, and not include the flag in the domain name field of the second domain name service request when the client identifier is not included in the domain name field of the second domain name service request.

6. (Cancelled)

7. (Currently amended) The data communications device of claim 6-3 wherein the controller further includes:

memory coupled to the processing circuitry, wherein the memory stores a list of domain names, and wherein the processing circuitry is further configured to access the list of domain names stored in the memory to determine whether the list of domain names includes an entry having the domain name, the domain name belonging to the predetermined group of domain names when the list of domain names includes an entry having the domain name, and the domain name not

belonging to the predetermined group of domain names when the list of domain name does not include an entry having the domain name.

8. (Currently amended) A data communications device, comprising:
an interface which is capable of communicating with a client; and
a controller coupled to the interface, wherein the controller includes:

means for intercepting a first domain name service request from the client;

means for providing a second domain name service request to a domain name service server through the interface in response to interception of the first domain name service request, the second domain name service request selectively (i) including a client identifier which identifies the client, and (ii) not including the client identifier which identifies the client, based on a selection decision; and

means for conveying a domain name service response from the domain name service server to the client through the interface, the domain name service response including a content server identifier which identifies a content server

wherein the first domain name service request includes a domain name field which contains a domain name, and wherein the controller includes:

means for generating, as the selection decision, a result having a first value when the domain name belongs to a predetermined group of domain names and a second value when the domain name does not belong to the predetermined group of domain names.

9. (Currently amended) A method for obtaining a domain name service on behalf of a client, the method comprising the steps of:
- intercepting a first domain name service request from the client;
 - in response to interception of the first domain name service request, providing a second domain name service request to a domain name service server which, based on a selection decision, selectively (i) includes a client identifier which identifies the client, and (ii) does not include the client identifier which identifies the client; and
 - conveying a domain name service response from the domain name service server to the client, the domain name service response including a content server identifier which identifies a content server,
- wherein the first domain name service request includes a domain name field which contains a domain name, and wherein the method further comprises the steps of:
- generating, as the selection decision, a result having a first value when the domain name belongs to a predetermined group of domain names and a second value when the domain name does not belong to the predetermined group of domain names.
10. (Original) The method of claim 9 wherein the second domain name service request includes a domain name field, and wherein the step of providing the second domain name service request includes the step of:
- based on the selection decision, selectively (i) including the client identifier in the domain name field of the second domain name service request, and (ii) not including the client identifier in the domain name field of the second domain name service request.

11. (Original) The method of claim 10 wherein the step of providing the second domain name service request further includes the step of:
 - including a flag in the domain name field of the second domain name service request when the client identifier is included in the domain name field of the second domain name service request, and not including the flag in the domain name field of the second domain name service request when the client identifier is not included in the domain name field of the second domain name service request.
12. (Cancelled)
13. (Currently amended) The method of claim ~~12~~9 wherein a memory stores a list of domain names, and wherein the step of generating the result includes the step of:
 - accessing the list of domain names stored in the memory to determine whether the list of domain names includes an entry having the domain name, the domain name belonging to the predetermined group of domain names when the list of domain names includes an entry having the domain name, and the domain name not belonging to the predetermined group of domain names when the list of domain names does not include an entry having the domain name.
14. (Currently amended) A computer program product that includes a computer readable medium having instructions stored thereon for obtaining a domain name service on behalf of a client, such that the instructions, when carried out by a computer, cause the computer to perform the steps of:
 - intercepting a first domain name service request from the client;
 - in response to interception of the first domain name service request, providing a second domain name service request to a domain

name service server which, based on a selection decision, selectively (i) includes a client identifier which identifies the client, and (ii) does not include the client identifier which identifies the client; and

conveying a domain name service response from the domain name service server to the client, the domain name service response including a content server identifier which identifies a content server,

wherein the first domain name service request includes a domain name field which contains a domain name, and wherein the instructions, when carried out by the computer, further cause the computer to perform the steps of:

generating, as the selection decision, a result having a first value when the domain name belongs to a predetermined group of domain names and a second value when the domain name does not belong to the predetermined group of domain names.

15. (Cancelled)

16. (Currently amended) A content distribution system according to claim ~~15~~1, wherein the second domain name service request includes a domain name field, and wherein the controller of the domain name service server includes:

processing circuitry which is configured to determine whether the domain name field of the second domain name service request includes a flag indicating that the domain name field includes the client identifier such that (i) selection of the content server identifier is based on the client identifier when the domain name field of the domain name service request includes the flag, and (ii) selection of the content server identifier is based on the data communications identifier when the domain name field of the domain name service request does not include the flag.

17. (Cancelled)
18. (Previously presented) A method according to claim 9, further comprising the steps of:
 - receiving the second domain name service request which includes a data communications device identifier identifying a data communications device;
 - selecting a content server identifier from a predetermined group of content server identifiers based on (i) the client identifier which identifies the client when the domain name service request further includes the client identifier, and (ii) the data communications device identifier when the domain name service request does not include the client identifier; and
 - providing the domain name service response having the selected content server identifier which identifies the content server.
19. (Previously Presented) The method of claim 18 wherein the second domain name service request includes a domain name field, and wherein the step of selecting the content server identifier includes the step of:
 - determining whether the domain name field of the domain name service request includes a flag indicating that the domain name field includes the client identifier such that (i) selection of the content server identifier is based on the client identifier when the domain name field of the domain name service request includes the flag, and (ii) selection of the content server identifier is based on the data communications identifier when the domain name field of the domain name service request does not include the flag.
20. (Cancelled)

21. (New) The content distribution system of claim 1 wherein the first domain name service request includes a domain name field which contains a domain name, and wherein the controller of the data communications device includes:

processing circuitry which is configured to generate, as the selection decision, a result having a first value when the domain name belongs to a predetermined group of domain names and a second value when the domain name does not belong to the predetermined group of domain names.

22. (New) The content distribution system of claim 21, wherein the predetermined group of domain names are domain names served by content servers identified by respective ones of the group of content identifiers among which the domain name service server selects.

23. (New) The data communications device of claim 3, wherein the predetermined group of domain names are domain names served by content servers which include the content server identified by the content server identifier of the domain name service response. .

24. (New) The data communications device of claim 8, wherein the predetermined group of domain names are domain names served by content servers which include the content server identified by the content server identifier of the domain name service response. .

25. (New) The method of claim 9, wherein the predetermined group of domain names are domain names served by content servers which include the content server identified by the content server identifier of the domain name service response.

26. (New) The computer program product of claim 14, wherein the predetermined group of domain names are domain names served by content servers which

include the content server identified by the content server identifier of the domain name service response.